


**SERIES:** VMS-130 | **DESCRIPTION:** AC-DC POWER SUPPLY

**FEATURES**


- 80 ~ 264 Vac input voltage range
- 2" x 3" open frame chassis
- 100 W power output with natural convection
- 130 W power output with forced air cooling
- active PFC
- IEC 60601-1 approved
- IEC Class I & Class II safety approved



| MODEL      | output voltage | output current <sup>1</sup> | output power <sup>2</sup> | ripple and noise <sup>3</sup> | efficiency <sup>4</sup> |
|------------|----------------|-----------------------------|---------------------------|-------------------------------|-------------------------|
|            | (Vdc)          | max (A)                     | max (W)                   | max (mVp-p)                   | typ (%)                 |
| VMS-130-12 | 12             | 10.8                        | 130                       | 120                           | 93                      |
| VMS-130-24 | 24             | 5.4                         | 130                       | 240                           | 93                      |
| VMS-130-36 | 36             | 3.6                         | 130                       | 360                           | 94                      |
| VMS-130-48 | 48             | 2.7                         | 130                       | 480                           | 94                      |

- Notes:
1. Maximum output power of 130 W with 10 CFM forced air cooling, and 100 W with natural convection. See derating curves.
  2. With forced air (10 CFM).
  3. At full load, nominal input, 20 MHz bandwidth oscilloscope with 10  $\mu$ F electrolytic and 0.1  $\mu$ F ceramic capacitors.
  4. At 230 Vac, 25°C, 75% load.

**PART NUMBER KEY**



## INPUT

| parameter       | conditions/description   | min | typ | max        | units  |
|-----------------|--------------------------|-----|-----|------------|--------|
| voltage         |                          | 80  |     | 264        | Vac    |
| frequency       |                          | 47  |     | 63         | Hz     |
| current         | at 240 Vac<br>at 100 Vac |     |     | 0.8<br>1.5 | A<br>A |
| inrush current  | at 240 Vac, cold start   |     |     | 100        | A      |
| leakage current |                          |     |     | 0.1        | mA     |

## OUTPUT

| parameter                  | conditions/description   | min | typ   | max | units |
|----------------------------|--------------------------|-----|-------|-----|-------|
| initial set point accuracy | at full load             |     | ±2    |     | %     |
| line regulation            | 100 ~ 240 Vac, full load |     | ±0.5  |     | %     |
| load regulation            | 10 ~ 100% load           |     | ±1    |     | %     |
| hold-up time               | at 230 Vac, 25°C         | 20  |       |     | ms    |
| temperature coefficient    |                          |     | ±0.05 |     | %/°C  |
| switching frequency        |                          |     | 105   |     | kHz   |

## PROTECTIONS

| parameter                | conditions/description  | min | typ | max                    | units                    |
|--------------------------|---|-----|-----|------------------------|--------------------------|
| over voltage protection  | auto recovery<br>12 Vdc output model<br>24 Vdc output model<br>36 Vdc output model<br>48 Vdc output model |     |     | 13.5<br>30<br>42<br>54 | Vdc<br>Vdc<br>Vdc<br>Vdc |
| short circuit protection | auto recovery, hiccup   |     |     |                        |                          |

## SAFETY & COMPLIANCE


| parameter                        | conditions/description  | min     | typ | max | units |
|----------------------------------|---|---------|-----|-----|-------|
| isolation voltage                | input to output   | 4,000   |     |     | Vac   |
| safety approvals                 | certified to 60601: IEC/EN/UL   |         |     |     |       |
| safety class                     | class I, class II   |         |     |     |       |
| conducted emissions              | EN55011 Class B when test condition is Class I, Class II  |         |     |     |       |
| radiated emissions               | EN55011 Class B when test condition is Class I<br>EN55011 Class A when test condition is Class II |         |     |     |       |
| harmonic current                 | IEC 61000-3-2   |         |     |     |       |
| voltage fluctuations and flicker | IEC 61000-3-3:2013  |         |     |     |       |
| ESD                              | IEC 61000-4-2   |         |     |     |       |
| radiated immunity                | IEC 61000-4-3   |         |     |     |       |
| EFT/burst                        | IEC 61000-4-4   |         |     |     |       |
| surge                            | IEC 61000-4-5   |         |     |     |       |
| conducted immunity               | IEC 61000-4-6   |         |     |     |       |
| voltage dips and interruptions   | IEC 61000-4-11  |         |     |     |       |
| MTBF                             | as per MIL-HDBK-217F at 25°C  | 400,000 |     |     | hours |
| RoHS                             | yes   |         |     |     |       |

## ENVIRONMENTAL


| parameter             | conditions/description | min | typ | max | units |
|-----------------------|------------------------|-----|-----|-----|-------|
| operating temperature | see derating curve     | -30 |     | 70  | °C    |
| storage temperature   |                        | -40 |     | 85  | °C    |
| operating humidity    | non-condensing         |     |     | 93  | %     |

## DERATING CURVES

**INPUT VOLTAGE DERATING CURVE**



**TEMPERATURE DERATING CURVE**



## MECHANICAL

| parameter  | conditions/description   | min | typ | max | units  |
|------------|--|-----|-----|-----|--------|
| dimensions | open frame models: 3.000 x 2.000 x 1.200 [76.2 x 50.8 x 30.5 mm] |     |     |     | inches |
|            | base plate models: 3.598 x 2.000 x 1.299 [91.4 x 50.8 x 33.0 mm] |     |     |     | inches |
|            | covered models: 3.598 x 2.520 x 1.358 [91.4 x 64.0 x 34.5 mm]    |     |     |     | inches |
| weight     | open frame models  |     | 135 |     | g      |
|            | base plate models  |     | 170 |     | g      |
|            | covered models   |     | 218 |     | g      |
| cooling    | natural convection (no integrated fan), see derating curve       |     | 100 |     | W      |
|            | 10 CFM   |     | 130 |     | W      |



## MECHANICAL DRAWING

### Open-frame

units: inch [mm]

general tolerance: ±0.02 [±0.5]

| PIN-OUT |          |
|---------|----------|
| PIN     | Function |
| 1       | AC (L)   |
| 2       | AC (N)   |
| 3       | -Vo      |
| 4       | -Vo      |
| 5       | +Vo      |
| 6       | +Vo      |




## MECHANICAL DRAWING (CONTINUED)

### Base plate

units: inch [mm]

general tolerance:  $\pm 0.02$  [ $\pm 0.5$ ]

| PIN-OUT |          |
|---------|----------|
| PIN     | Function |
| 1       | AC (L)   |
| 2       | AC (N)   |
| 3       | -Vo      |
| 4       | -Vo      |
| 5       | +Vo      |
| 6       | +Vo      |




## MECHANICAL DRAWING (CONTINUED)

**Covered**

units: inch [mm]

general tolerance:  $\pm 0.02$  [ $\pm 0.5$ ]

| PIN-OUT |          |
|---------|----------|
| PIN     | Function |
| 1       | AC (L)   |
| 2       | AC (N)   |
| 3       | -Vo      |
| 4       | -Vo      |
| 5       | +Vo      |
| 6       | +Vo      |



## REVISION HISTORY

---

| rev. | description                | date       |
|------|----------------------------|------------|
| 1.0  | initial release            | 11/09/2021 |
| 1.01 | mechanical drawing updated | 07/13/2022 |
| 1.02 | medical icon added         | 05/04/2023 |

The revision history provided is for informational purposes only and is believed to be accurate.



**CUI INC**  
a bel group

**Headquarters**  
20050 SW 112th Ave.  
Tualatin, OR 97062  
**800.275.4899**

Fax 503.612.2383  
**cui.com**  
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.